



■ Features :

- 12V or 24V DC input
- Power ON-OFF switch
- Input voltage range: -15% ~ +25%
- Output voltage regulation: ±10%
- Protections: Bat. Low alarm/Bat. Low shutdown/Over voltage/Over temp./Output shout/Input polarity reverse/Over load.
- Output waveform: Modified sine wave
- Cooling fan ON-OFF control
- ON/OFF remote control(Optional)
- Approvals: e13/ CE
- 1 year warranty



**SPECIFICATION**

ORDER NO.	A301-2K5-B2	A301-2K5-F3	A302-2K5-B2	A302-2K5-F3	
OUTPUT	SAFETY MODEL NO. A-300-2K5W				
	AC VOLTAGE	110V	230V	110V	230V
	RATED POWER	2500W			
	SURGE POWER	5000W			
	WAVEFORM	Modified Sine Wave			
	FREQUENCY	60Hz±1%	50Hz±1%	60Hz±1%	50Hz±1%
	AC REGULATION	±10%		±10%	
	STANDARD RECEPTACLES	TYPE-2* 2ea	TYPE-3* 2ea	TYPE-2* 2ea	TYPE-3* 2ea
LED INDICATOR	Green LED for power on; Yellow LED for O.T.P.; Red LED for O.L.P.; Battery V/A meter				
INPUT	DC CURRENT	250A		130A	
	NO LOAD CURRENT DRAW	0.9A		0.6A	
	DC VOLTAGE	12V		24V	
	VOLTAGE RANGE	10 ~ 15VDC		21 ~ 30VDC	
	EFFICIENCY (Typ.)	90%		90%	
	DC CONNECTOR	None		None	
	FUSE	30A*12		15A*12	
PROTECTION	BAT. LOW ALARM	10±0.5V		21±0.8V	
	BAT. LOW SHUTDOWN	9.5±0.5V		20±0.8V	
	OVER LOAD	>2700W shut down o/p voltage, re-power to recover			
	OVER VOLTAGE	15 ~ 17V		30 ~ 32V	
	OVER TEMPERATURE	60±5°C / 140±9°F			
	OUTPUT SHORT	Shut-off			
BAT. POLARITY	By fuse open				
ENVIRONMENT	WORKING TEMP.	0 ~ +25°C @100% load			
	WORKING HUMIDITY	20% ~ 90% RH non-condensing			
	STORAGE TEMP., HUMIDITY	-30~+70°C / -22~+158°F, 10~95% RH			
	TEMP. COEFFICIENT	±0.05% / °C (0~50°C)			
SAFETY & EMC	ISOLATION RESISTANCE	I/P-O/P: 100M Ohms / 500VDC			
	EMI CONDUCTION & RADIATION	Compliance to EN55022 class B, 72/ 245/ CEE, 95/ 54/ CE			
	EMS IMMUNITY	Compliance to EN61000-4-2,3			
	LVD	Compliance to EN60950			
OTHERS	MTBF	37Khrs min. MIL-HDBK-217F (25°C)			
	DIMENSION	430*210*159mm (L*W*H)			
	PACKING	8.7kg ; 2pcs / 19kg / CARTON			
	COOLING	>40°C (NTC) fan on			
	APPLICATIONS	Home appliance, Power tools, Office and Portable equipment and Vehicle ...etc.			

■ AC Output Receptacles (optional)

TYPE-1	TYPE-2	TYPE-3	TYPE-4	TYPE-5	TYPE-6
JAPAN	USA	EUROPE	UNIVERSAL	AUSTRALIA	U.K

## Mechanical Specification

Unit:mm

